

# Directory Search Results

---

WRAS Approval Number: 2107030

Approved Product

Single hole, single outlet (fixed) combination tap assembly with a brushed stainless-steel body, incorporating a ceramic cartridge headwork with a single lever operating member. The spout outlet incorporates a plastic aerator. Maximum working pressure 5.0 bar. Maximum operating temperature 60°C.

- **Section:** 0450 Combination Tap Assemblies (?section=0450)
- **Section Subtitle:** Single hole, metal single outlet, fixed. Taps used in high risk installations, such as kitchen sinks, are considered to be a fluid category 5 risk. Backflow protection is usually provided in the form of an AUK3 tap gap. Where an AUK3 tap gap cannot be maintained, for example where the tap gap is compromised as a result of:
  - the tap being lowered in any way;
  - adjustment to the spout which reduces the distance between the tap outlet and spillover level of the sink;
  - or the operation of a pull out hose attachment;alternative fluid category 5 backflow protection is required.
- **WRAS Approval Number:** 2107030
- **Expiry date:** 31/07/2026
- **Size:** Stainless steel braided silicone lined flexible hose assemblies incorporating 3/8" captive nut end connections.
- **Marking:** Treemme on operating member.
- **Installation Requirements R001**  
(/approvals/resources/fittings/installation\_requirements/irn\_r001)R006  
(/approvals/resources/fittings/installation\_requirements/irn\_r006)R009  
(/approvals/resources/fittings/installation\_requirements/irn\_r009)R010  
(/approvals/resources/fittings/installation\_requirements/irn\_r010)
- **Model**  
5MM (IT2811IS5MZZ).
- **Manufacturer:** Rubinetterie 3M S.r.l. View All Listings by this Company (?company=17774)